

System: Host: antix1 Kernel: 5.8.16-antix.1-amd64-smp x86_64 bits: 64 compiler:
N/A
parameters: BOOT_IMAGE=/boot/vmlinuz-5.8.16-antix.1-amd64-smp
root=UUID=2310738f-8a5a-4dee-a14f-c0ec6c3a93a6 ro vga=0x0317 quiet
Desktop: IceWM 2.0.1 dm: SLiM 1.3.6
Distro: antiX-19.3_x64-full Manolis Glezos 15 October 2020
base: Debian GNU/Linux 10 (buster)

Machine: Type: Desktop Mobo: HUANANZHI model: X79 v: VAA1 serial: <filter>
BIOS: American Megatrends v: 4.6.5 date: 07/07/2018

Memory: RAM: total: 31.30 GiB used: 715.5 MiB (2.2%)
RAM Report: permissions: Unable to run dmidecode. Root privileges
required.

PCI Slots: Permissions: Unable to run dmidecode. Root privileges required.

CPU: Topology: 2x Quad Core model: Intel Xeon E5-2609 0 bits: 64 type: MCP
SMP
arch: Sandy Bridge family: 6 model-id: 2D (45) stepping: 7 microcode:
71A
L2 cache: 20.0 MiB bogomips: 38430
Speed: 1377 MHz min/max: 1200/2400 MHz Core speeds (MHz): 1: 1594 2:
1200 3: 1311
4: 1200 5: 1701 6: 1839 7: 2079 8: 2146
Flags: acpi aes aperfmperf apic arat arch_perfmon avx bts clflush cmov
constant_tsc
cpuid cx16 cx8 dca de ds_cpl dtes64 dtherm dts epb ept est flexpriority
flush_lldt fpu
fxsr ht ibpb ibrs lahfm lm mca mce md_clear mmx monitor msr mtrr
nonstop_tsc nopl nx
pae pat pbe pcid pclmulqdq pdcm pdpe1gb pebs pge pln pni popcnt pse
pse36 pti pts
rdtscp rep_good sep smx ss ssbd sse sse2 sse4_1 sse4_2 ssse3 stibp
syscall tm tm2
tpr_shadow tsc tsc_deadline_timer vme vmx vnmi vpid x2apic xsave
xsaveopt xtopology
xtpr
Vulnerabilities: Type: itlb_multihit status: KVM: VMX disabled
Type: l1tf mitigation: PTE Inversion; VMX: conditional cache flushes,
SMT disabled
Type: mds mitigation: Clear CPU buffers; SMT disabled
Type: meltdown mitigation: PTI
Type: spec_store_bypass
mitigation: Speculative Store Bypass disabled via prctl and seccomp
Type: spectre_v1 mitigation: usercopy/swapgs barriers and __user
pointer sanitization
Type: spectre_v2 mitigation: Full generic retpoline, IBPB: conditional,
IBRS_FW, STIBP:
disabled, RSB filling
Type: srbds status: Not affected
Type: tsx_async_abort status: Not affected

Graphics: Device-1: NVIDIA GT218 [GeForce 210] driver: N/A bus ID: 03:00.0 chip
ID: 10de:0a65
Display: x11 server: X.Org 1.20.4 driver: vesa resolution: 1024x768~N/A
OpenGL: renderer: llvmpipe (LLVM 7.0 256 bits) v: 3.3 Mesa 18.3.6
compat-v: 3.1
direct render: Yes

Audio: Device-1: Intel C600/X79 series High Definition Audio driver:
snd_hda_intel v: kernel
bus ID: 00:1b.0 chip ID: 8086:1d20
Device-2: NVIDIA High Definition Audio driver: snd_hda_intel v: kernel

bus ID: 03:00.1
chip ID: 10de:0be3
Sound Server: ALSA v: k5.8.16-antix.1-amd64-smp
Network: Device-1: Realtek RTL8111/8168/8411 PCI Express Gigabit Ethernet
driver: r8169
v: kernel port: 6000 bus ID: 08:00.0 chip ID: 10ec:8168
IF: eth0 state: down mac: <filter>
Device-2: Intel Wi-Fi 6 AX200 driver: iwlwifi v: kernel port: 6000 bus
ID: 0a:00.0
chip ID: 8086:2723
IF: wlan1 state: up mac: <filter>
IP v4: <filter> type: dynamic scope: global broadcast: <filter>
IP v6: <filter> scope: link
Device-3: Realtek RTL8111/8168/8411 PCI Express Gigabit Ethernet
driver: r8169
v: kernel port: 5000 bus ID: 0b:00.0 chip ID: 10ec:8168
IF: eth1 state: down mac: <filter>
WAN IP: <filter>
Drives: Local Storage: total: 1.82 TiB used: 27.21 GiB (1.5%)
ID-1: /dev/sda vendor: Seagate model: ST500DM002-1ER14C size: 465.76
GiB block size:
physical: 4096 B logical: 512 B speed: 6.0 Gb/s rotation: 7200 rpm
serial: <filter>
rev: CC45 scheme: MBR
ID-2: /dev/sdb vendor: Seagate model: ST3500413AS size: 465.76 GiB
block size:
physical: 512 B logical: 512 B speed: 6.0 Gb/s rotation: 7200 rpm
serial: <filter>
rev: JC45 scheme: MBR
ID-3: /dev/sdc vendor: Seagate model: ST3500418AS size: 465.76 GiB
block size:
physical: 512 B logical: 512 B speed: 3.0 Gb/s rotation: 7200 rpm
serial: <filter>
rev: HP40 scheme: MBR
ID-4: /dev/sdd vendor: Seagate model: ST500DM002-1BD142 size: 465.76
GiB block size:
physical: 4096 B logical: 512 B speed: 3.0 Gb/s rotation: 7200 rpm
serial: <filter>
rev: KC65 scheme: MBR
ID-5: /dev/sde vendor: ASMedia model: T109x- Config size: 100.0 MiB
block size:
physical: 512 B logical: 512 B speed: 6.0 Gb/s rotation: 7200 rpm
serial: <filter>
rev: n/a
Optical-1: /dev/sr0 vendor: TSSTcorp model: DVD+-RW TS-H653G rev: DW10
dev-links: cdrom,cdrw,dvd,dvdrw
Features: speed: 48 multisession: yes audio: yes dvd: yes rw: cd-r,cd-
rw,dvd-r,dvd-ram
state: running
RAID: Message: No RAID data was found.
Partition: ID-1: / raw size: 48.83 GiB size: 47.81 GiB (97.92%) used: 6.92 GiB
(14.5%) fs: ext4
dev: /dev/sda1 label: rootantiX19 uuid: 2310738f-8a5a-4dee-a14f-
c0ec6c3a93a6
ID-2: /home raw size: 200.20 GiB size: 196.05 GiB (97.93%) used: 20.29
GiB (10.3%)
fs: ext4 dev: /dev/sda6 label: homeantiX uuid: 231afe95-3cba-4993-beb1-
b52726510965

```

ID-3: swap-1 size: 11.72 GiB used: 0 KiB (0.0%) fs: swap swappiness: 10
(default 60)
cache pressure: 50 (default 100) dev: /dev/sda5 label: swap
uuid: 1540a43b-5380-407b-a657-be4b262d6e04
Unmounted: ID-1: /dev/sda2 size: 1 KiB fs: <root required> label: N/A uuid: N/A
ID-2: /dev/sda7 size: 205.02 GiB fs: ext4 label: antix_data
uuid: 3eedced4-3153-41ef-9147-953c4a5795fe
ID-3: /dev/sdb1 size: 232.67 GiB fs: ext4 label: sdb1
uuid: 0a085231-c321-49d4-aaf0-9d7f71cf067d
ID-4: /dev/sdb2 size: 233.09 GiB fs: ext4 label: sdb2
uuid: 7cf9bdcd-a2e9-493c-90f7-68cbd17af463
ID-5: /dev/sdc1 size: 232.88 GiB fs: ext4 label: sdc1
uuid: a8aca46c-d144-456c-93ae-39bc84a527c9
ID-6: /dev/sdc2 size: 232.88 GiB fs: ext4 label: sdc2
uuid: 8b2f7fe4-ac6f-406e-a4e4-8e9e0ab2d50c
ID-7: /dev/sdd1 size: 232.88 GiB fs: ext4 label: sdd1
uuid: f949503c-76cd-4b06-ade0-fc54a756915a
ID-8: /dev/sdd2 size: 232.88 GiB fs: ext4 label: sdd2
uuid: 198b6b77-a1e4-4adf-b340-98a24491a44e
USB:
Hub: 1-0:1 info: Full speed (or root) Hub ports: 2 rev: 2.0 speed: 480
Mb/s
chip ID: 1d6b:0002
Hub: 1-1:2 info: Intel Integrated Rate Matching Hub ports: 6 rev: 2.0
speed: 480 Mb/s
chip ID: 8087:0024
Device-1: 1-1.1:3 info: Pixart Imaging Optical Mouse type: Mouse
driver: hid-generic,usbhid interfaces: 1 rev: 1.1 speed: 1.5 Mb/s chip
ID: 093a:2510
Device-2: 1-1.2:4 info: N/A type: Keyboard,HID driver: hid-
generic,usbhid interfaces: 2
rev: 1.1 speed: 1.5 Mb/s chip ID: c0f4:01e0
Device-3: 1-1.3:5 info: Intel type: Bluetooth driver: btusb interfaces:
2 rev: 2.0
speed: 12 Mb/s chip ID: 8087:0029
Hub: 2-0:1 info: Full speed (or root) Hub ports: 2 rev: 2.0 speed: 480
Mb/s
chip ID: 1d6b:0002
Hub: 2-1:2 info: Intel Integrated Rate Matching Hub ports: 8 rev: 2.0
speed: 480 Mb/s
chip ID: 8087:0024
Hub: 2-1.2:3 info: Terminus FE 2.1 7-port Hub ports: 7 rev: 2.0 speed:
480 Mb/s
chip ID: 1a40:0201
Device-4: 2-1.2.2:4 info: Genesys Logic Logilink CR0012 type: Mass
Storage
driver: usb-storage interfaces: 1 rev: 2.0 speed: 480 Mb/s chip ID:
05e3:0745
serial: <filter>
Hub: 3-0:1 info: Full speed (or root) Hub ports: 1 rev: 2.0 speed: 480
Mb/s
chip ID: 1d6b:0002
Hub: 3-1:2 info: VIA Labs Hub ports: 4 rev: 2.1 speed: 480 Mb/s chip
ID: 2109:3431
Hub: 4-0:1 info: Full speed (or root) Hub ports: 4 rev: 3.0 speed: 5
Gb/s
chip ID: 1d6b:0003
Sensors: System Temperatures: cpu: 33.0 C mobo: N/A
Fan Speeds (RPM): N/A

```

Repos: Active apt repos in: /etc/apt/sources.list.d/antix.list
1: deb http://ftp.cica.es/mirrors/Linux/MX-Packages/antix/buster
buster main nonfree nosystemd
Active apt repos in: /etc/apt/sources.list.d/buster-backports.list
1: deb http://deb.debian.org/debian buster-backports main contrib non-
free
Active apt repos in: /etc/apt/sources.list.d/debian-stable-updates.list
1: deb http://ftp.pt.debian.org/debian/ buster-updates main contrib
non-free
Active apt repos in: /etc/apt/sources.list.d/debian.list
1: deb http://ftp.pt.debian.org/debian/ buster main contrib non-free
2: deb http://security.debian.org/ buster/updates main contrib non-
free
Active apt repos in: /etc/apt/sources.list.d/google-earth-pro.list
1: deb [arch=amd64] http://dl.google.com/linux/earth/deb/ stable main
No active apt repos in: /etc/apt/sources.list.d/onion.list
No active apt repos in: /etc/apt/sources.list.d/various.list
Processes: CPU top: 5
1: cpu: 12.0% command: yad pid: 19581 mem: 26.8 MiB (0.0%)
2: cpu: 4.3% command: chromium pid: 4548 mem: 270.8 MiB (0.8%)
3: cpu: 4.2% command: chromium pid: 4601 mem: 177.5 MiB (0.5%)
4: cpu: 2.6% command: chromium pid: 19037 mem: 178.1 MiB (0.5%)
5: cpu: 1.8% command: xorg pid: 2817 mem: 73.5 MiB (0.2%)
Memory top: 5
1: mem: 270.8 MiB (0.8%) command: chromium pid: 4548 cpu: 4.3%
2: mem: 213.2 MiB (0.6%) command: chromium pid: 4604 cpu: 1.5%
3: mem: 178.1 MiB (0.5%) command: chromium pid: 19037 cpu: 2.6%
4: mem: 177.5 MiB (0.5%) command: chromium pid: 4601 cpu: 4.2%
5: mem: 139.3 MiB (0.4%) command: chromium pid: 4650 cpu: 0.0%
Info: Processes: 225 Uptime: 1h 26m Init: SysVinit v: 2.93 runlevel: 5
default: 5 Compilers:
gcc: 8.3.0 alt: 8 Client: shell wrapper v: 5.0.3-release inxi: 3.0.36