

System: Host: antix1 Kernel: 5.10.27-antix.1-amd64-smp x86_64 bits: 64 compiler: N/A
parameters: BOOT_IMAGE=/boot/vmlinuz-5.10.27-antix.1-amd64-smp
root=UUID=95839a0e-968c-4821-bb3f-de144d61a603 ro quiet
Desktop: IceWM 2.3.2 dm: SLiM 1.3.6
Distro: antiX-19.3 x64-full Manolis Glezos 16 October 2020
base: Debian GNU/Linux 10 (buster)

Machine: Type: Desktop Mobo: N/A model: Intel X79 serial: <filter> BIOS: American Megatrends
v: X79DT00A date: 01/13/2020

Memory: RAM: total: 15.55 GiB used: 416.1 MiB (2.6%)
RAM Report: permissions: Unable to run dmidecode. Root privileges required.

PCI Slots: Permissions: Unable to run dmidecode. Root privileges required.

CPU: Topology: 2x 6-Core model: Intel Xeon E5-2620 0 bits: 64 type: MT MCP SMP
arch: Sandy Bridge family: 6 model-id: 2D (45) stepping: 7 microcode: 71A
L2 cache: 30.0 MiB bogomips: 96096
Speed: 1826 MHz min/max: 1200/2500 MHz Core speeds (MHz): 1: 1294 2: 1265 3: 1200
4: 1200 5: 1474 6: 1264 7: 1253 8: 1268 9: 1513 10: 1889 11: 1200 12: 1200 13: 1477
14: 1200 15: 1200 16: 1200 17: 1200 18: 1496 19: 1462 20: 1560 21: 1200 22: 1200
23: 1200 24: 1200
Flags: acpi aes aperfmperf apic arat arch_perfmon avx bts clflush cmov constant_tsc
cpuid cx16 cx8 dca de ds_cpl dtes64 dtherm dts epb ept est flexpriority flush_lldt fpu
fxsr ht ibpb ibrs ida lahf_lm lm mca mce md_clear mmx monitor msr mtrr nonstop_tsc nopl
nx pae pat pbe pcid pclmulqdq pdcms pdpe1gb pebs pge pln pni popcnt pse pse36 pti pts
rdtscp rep_good sep smx ss sbsd sse sse2 sse4_1 sse4_2 ssse3 stibp syscall tm tm2
tpr_shadow tsc tsc_deadline_timer vme vmx vnm1 vpuid x2apic xsave xsaveopt xtopology
xtpr
Vulnerabilities: Type: itlb_multihit status: KVM: VMX disabled
Type: l1tf mitigation: PTE Inversion; VMX: conditional cache flushes, SMT vulnerable
Type: mds mitigation: Clear CPU buffers; SMT vulnerable
Type: meltdown mitigation: PTI
Type: spec_store_bypass
mitigation: Speculative Store Bypass disabled via prctl and seccomp
Type: spectre_v1 mitigation: usercopy/swaps barriers and __user pointer sanitization
Type: spectre_v2 mitigation: Full generic retpoline, IBPB: conditional, IBRS_FW, STIBP:
conditional, RSB filling
Type: srbds status: Not affected
Type: tsx_async_abort status: Not affected

Graphics: Device-1: AMD Cedar [Radeon HD 5000/6000/7350/8350 Series] vendor: PC Partner Limited
driver: radeon v: kernel bus ID: 03:00.0 chip ID: 1002:68f9
Display: x11 server: X.Org 1.20.4 driver: ati,radeon unloaded: fbdev,modesetting,vesa
resolution: 1024x768~85Hz
OpenGL: renderer: AMD CEDAR (DRM 2.50.0 / 5.10.27-antix.1-amd64-smp LLVM 7.0.1)
v: 3.3 Mesa 18.3.6 compat-v: 3.1 direct render: Yes

Audio: Device-1: Intel C600/X79 series High Definition Audio driver: snd_hda_intel v: kernel
bus ID: 00:1b.0 chip ID: 8086:1d20
Device-2: AMD Cedar HDMI Audio [Radeon HD 5400/6300/7300 Series]
vendor: PC Partner Limited driver: snd_hda_intel v: kernel bus ID: 03:00.1
chip ID: 1002:aa68
Sound Server: ALSA v: k5.10.27-antix.1-amd64-smp

Network: Device-1: Realtek RTL8111/8168/8411 PCI Express Gigabit Ethernet driver: r8169
v: kernel port: 4000 bus ID: 08:00.0 chip ID: 10ec:8168
IF: eth0 state: down mac: <filter>
IF-ID-1: wlan0 state: up mac: <filter>
IP v4: <filter> type: dynamic scope: global broadcast: <filter>
IP v6: <filter> scope: link
WAN IP: <filter>

Drives: Local Storage: total: 754.56 GiB used: 68.06 GiB (9.0%)
ID-1: /dev/sda model: SGT S800 60GB SSD size: 55.90 GiB block size: physical: 512 B
logical: 512 B speed: 6.0 Gb/s serial: <filter> rev: 1A scheme: MBR
ID-2: /dev/sdb vendor: Seagate model: ST3250318AS size: 232.89 GiB block size:
physical: 512 B logical: 512 B speed: 3.0 Gb/s rotation: 7200 rpm serial: <filter>
rev: CC38 scheme: MBR
ID-3: /dev/sdc vendor: Seagate model: ST3250318AS size: 232.89 GiB block size:
physical: 512 B logical: 512 B speed: 3.0 Gb/s rotation: 7200 rpm serial: <filter>
rev: CC44 scheme: MBR
ID-4: /dev/sdd vendor: Seagate model: ST3250318AS size: 232.89 GiB block size:
physical: 512 B logical: 512 B speed: 3.0 Gb/s rotation: 7200 rpm serial: <filter>
rev: CC38 scheme: MBR
Optical-1: /dev/sr0 vendor: HL-DT-ST model: DVD-RAM GH24NSD5 rev: LV00
dev-links: cdrom,cdrw,dvd,dvdrw
Features: speed: 12 multisession: yes audio: yes dvd: yes rw: cd-r,cd-rw,dvd-r,dvd-ram
state: running

RAID: Message: No RAID data was found.

Partition: ID-1: / raw size: 50.04 GiB size: 49.00 GiB (97.93%) used: 5.52 GiB (11.3%) fs: ext4
dev: /dev/sda2 label: rootantiX19 uuid: 95839a0e-968c-4821-bb3f-de144d61a603
ID-2: /home raw size: 232.88 GiB size: 228.23 GiB (98.00%) used: 45.92 GiB (20.1%)
fs: ext4 dev: /dev/sdb1 label: homeantiX uuid: 923dd82b-7459-48e9-8a5a-4db22978713c
ID-3: /media/sdc1 raw size: 116.41 GiB size: 113.59 GiB (97.57%) used: 59.6 MiB (0.1%)
fs: ext4 dev: /dev/sdc1 label: sdc1 uuid: 7060fea0-7d6d-4fa9-ab10-ba5bffff0ca
ID-4: /media/sdc2 raw size: 116.47 GiB size: 114.14 GiB (98.00%) used: 59.6 MiB (0.1%)
fs: ext4 dev: /dev/sdc2 label: sdc2 uuid: a1924fbc-b070-4508-8852-211bde378f5f
ID-5: /media/sdd1 raw size: 116.21 GiB size: 113.89 GiB (98.00%) used: 59.6 MiB (0.1%)
fs: ext4 dev: /dev/sdd1 label: sdd1 uuid: 088f9375-073a-479e-8f41-b23ba12d2df7
ID-6: /media/sdd2 raw size: 116.67 GiB size: 114.34 GiB (98.00%)

used: 16.45 GiB (14.4%) fs: ext4 dev: /dev/sdd2 label: sdd2
uuid: 1cfa8c8b-3fd0-4061-8315-cbfb073f3068
ID-7: swap-1 size: 5.86 GiB used: 0 KiB (0.0%) fs: swap swappiness: 10 (default 60)
cache pressure: 50 (default 100) dev: /dev/sdal label: swap
uuid: 2f06d8b4-bb5e-439d-8d9a-34ea616ad976

Unmounted: Message: No unmounted partitions found.

USB:

Hub: 1-0:1 info: Full speed (or root) Hub ports: 2 rev: 2.0 speed: 480 Mb/s
chip ID: 1d6b:0002
Hub: 1-1:2 info: Full speed (or root) Hub ports: 6 rev: 2.0 speed: 480 Mb/s
chip ID: 8087:0024
Device-1: 1-1.3:3 info: N/A type: Network driver: ath9k_htc interfaces: 1 rev: 2.0
speed: 480 Mb/s chip ID: 0cf3:9271 serial: <filter>
Hub: 1-1.5:4 info: Full speed (or root) Hub ports: 3 rev: 2.0 speed: 12 Mb/s
chip ID: 0a5c:4500
Device-2: 1-1.5.3:7 info: N/A type: <vendor specific> driver: btusb interfaces: 4
rev: 2.0 speed: 12 Mb/s chip ID: 05ac:828b
Hub: 2-0:1 info: Full speed (or root) Hub ports: 2 rev: 2.0 speed: 480 Mb/s
chip ID: 1d6b:0002
Hub: 2-1:2 info: Full speed (or root) Hub ports: 8 rev: 2.0 speed: 480 Mb/s
chip ID: 8087:0024
Device-3: 2-1.3:3 info: N/A type: Mouse driver: hid-generic,usbhid interfaces: 1
rev: 2.0 speed: 1.5 Mb/s chip ID: 046d:c050
Device-4: 2-1.4:4 info: N/A type: Keyboard,HID driver: hid-generic,usbhid interfaces: 2
rev: 1.1 speed: 1.5 Mb/s chip ID: 040b:2000
Hub: 2-1.7:5 info: Hi-speed hub with multiple TTs ports: 7 rev: 2.0 speed: 480 Mb/s
chip ID: 1a40:0201
Device-5: 2-1.7.2:6 info: N/A type: Mass Storage driver: usb-storage interfaces: 1
rev: 2.0 speed: 480 Mb/s chip ID: 05e3:0745 serial: <filter>
Hub: 3-0:1 info: Full speed (or root) Hub ports: 1 rev: 2.0 speed: 480 Mb/s
chip ID: 1d6b:0002
Hub: 3-1:2 info: Full speed (or root) Hub ports: 4 rev: 2.1 speed: 480 Mb/s
chip ID: 2109:3431
Hub: 4-0:1 info: Full speed (or root) Hub ports: 4 rev: 3.0 speed: 5 Gb/s
chip ID: 1d6b:0003

Sensors: System Temperatures: cpu: 66.0 C mobo: N/A gpu: radeon temp: 44 C
Fan Speeds (RPM): N/A

Repos: Active apt repos in: /etc/apt/sources.list.d/antix.list
1: deb https://anorien.csc.warwick.ac.uk/mxlinux/packages/antix/buster/ buster main nonfree nosystemd
Active apt repos in: /etc/apt/sources.list.d/buster-backports.list
1: deb http://deb.debian.org/debian buster-backports main contrib non-free
Active apt repos in: /etc/apt/sources.list.d/debian-stable-updates.list
1: deb http://ftp.pt.debian.org/debian/ buster-updates main contrib non-free
Active apt repos in: /etc/apt/sources.list.d/debian.list
1: deb http://ftp.pt.debian.org/debian/ buster main contrib non-free
2: deb http://security.debian.org/ buster/updates main contrib non-free
No active apt repos in: /etc/apt/sources.list.d/onion.list
Active apt repos in: /etc/apt/sources.list.d/skype-stable.list
1: deb [arch=amd64] https://repo.skype.com/deb stable main
No active apt repos in: /etc/apt/sources.list.d/various.list

Processes: CPU top: 5
1: cpu: 5.9% command: xorg pid: 3041 mem: 53.5 MiB (0.3%)
2: cpu: 5.3% command: init pid: 1 mem: 2.03 MiB (0.0%)
3: cpu: 3.8% command: gtkdialog pid: 4380 mem: 29.2 MiB (0.1%)
4: cpu: 3.0% command: clipit pid: 3866 mem: 57.6 MiB (0.3%)
5: cpu: 2.8% command: yad pid: 3874 mem: 55.7 MiB (0.3%)
Memory top: 5
1: mem: 57.6 MiB (0.3%) command: clipit pid: 3866 cpu: 3.0%
2: mem: 55.7 MiB (0.3%) command: yad pid: 3874 cpu: 2.8%
3: mem: 53.5 MiB (0.3%) command: xorg pid: 3041 cpu: 5.9%
4: mem: 30.4 MiB (0.1%) command: yad pid: 4407 cpu: 0.0%
5: mem: 29.2 MiB (0.1%) command: gtkdialog pid: 4380 cpu: 3.8%

Info: Processes: 376 Uptime: N/A Init: SysVinit v: 2.93 runlevel: 5 default: 5 Compilers:
gcc: 8.3.0 alt: 8 Client: shell wrapper v: 5.0.3-release inxi: 3.0.36