

System:

Kernel: 5.10.57-antix.1-amd64-smp arch: x86_64 bits: 64 compiler: gcc v: 10.2.1
parameters: BOOT_IMAGE=/boot/vmlinuz-5.10.57-antix.1-amd64-smp
root=UUID=cca17cef-eb62-4687-abaa-49aa35a27503 ro quiet

Desktop: IceWM v: 2.9.7 vt: 7 dm: slimski v: 1.5.0

Distro: antiX-21_x64-full Grup Yorum 31 October 2021 base: Debian

GNU/Linux 11 (bullseye)

Machine:

Type: Desktop System: Apple product: iMac7,1 v: 1.0 serial: <superuser required> Chassis:

type: 13 v: Mac-F42386C8 serial: <superuser required>

Mobo: Apple model: Mac-F42386C8 v: PVT serial: <superuser required> UEFI: Apple

v: IM71.88Z.007A.B03.0803051705 date: 03/05/08

Battery:

Message: No system battery data found. Is one present?

Memory:

RAM: total: 1.93 GiB used: 985.2 MiB (49.7%)

RAM Report: permissions: Unable to run dmidecode. Root privileges required.

PCI Slots:

Permissions: Unable to run dmidecode. Root privileges required.

CPU:

Info: model: Intel Core2 Extreme X7900 bits: 64 type: MCP arch: Core2 Merom
built: 2006-09

process: Intel 65nm family: 6 model-id: 0xF (15) stepping: 0xB (11) microcode: 0xBA

Topology: cpus: 1x cores: 2 smt: <unsupported> cache: L1: 128 KiB desc: d-2x32 KiB; i-2x32 KiB

L2: 4 MiB desc: 1x4 MiB

Speed (MHz): avg: 2383 high: 2459 min/max: 800/2800 scaling: driver: acpi-cpufreq

governor: performance cores: 1: 2459 2: 2307 bogomips: 11171

Flags: acpi aperfmperf apic arch_perfmon bts clflush cmov constant_tsc cpuid
cx16 cx8 de

ds_cpl dtes64 dtherm dts est flexpriority fpu fxsr ht lahf_lm lm mca mce mmx
monitor msr mtrr

nopl nx pae pat pbe pdcm pebs pge pni pse pse36 pti rep_good sep sse sse2
ssse3 syscall tm tm2

tpr_shadow tsc vme vmx vnmi vpid xtp

Vulnerabilities:

Type: itlb_multihit status: KVM: VMX disabled

Type: l1tf mitigation: PTE Inversion; VMX: EPT disabled

Type: mds status: Vulnerable: Clear CPU buffers attempted, no microcode; SMT disabled

Type: meltdown mitigation: PTI

Type: spec_store_bypass status: Vulnerable

Type: spectre_v1 mitigation: usercopy/swapgs barriers and __user pointer sanitization

Type: spectre_v2 mitigation: Full generic retpoline, STIBP: disabled, RSB filling
Type: srbds status: Not affected
Type: tsx_async_abort status: Not affected
Graphics:
Device-1: AMD RV630/M76 [Mobility Radeon HD 2600 XT/2700] vendor: Apple
iMac 7 1 driver: radeon
v: kernel arch: R500 process: TSMC 90nm built: 2005-07 pcie: gen: 1 speed:
2.5 GT/s lanes: 16
ports: active: LVDS-1 empty: DIN-1,DVI-I-1 bus-ID: 01:00.0 chip-ID: 1002:9583
class-ID: 0300
Device-2: Apple Built-in iSight type: USB driver: uvcvideo bus-ID: 2-4:3 chip-ID:
05ac:8502
class-ID: 0e02 serial: <filter>
Display: x11 server: X.Org v: 1.20.11 driver: X: loaded: radeon
unloaded: fbdev,modesetting,vesa gpu: radeon display-ID: :0.0 screens: 1
Screen-1: 0 s-res: 1920x1200 s-dpi: 96 s-size: 508x317mm (20.00x12.48") s-
diag: 599mm (23.57")
Monitor-1: LVDS-1 mapped: LVDS model: Apple Color LCD serial: <filter> built:
2007
res: 1920x1200 hz: 60 dpi: 151 gamma: 1.2 chroma: red: x: 0.639 y: 0.341
green: x: 0.290
y: 0.616 blue: x: 0.145 y: 0.067 white: x: 0.314 y: 0.329 size: 324x262mm
(12.76x10.31")
diag: 611mm (24") ratio: 16:10, 15:9 modes: 1920x1200, 1920x1080,
1600x1200, 1680x1050,
1400x1050, 1280x1024, 1440x900, 1280x960, 1280x854, 1280x800,
1280x720, 1152x768, 1024x768,
800x600, 848x480, 720x480, 640x480
EDID-Warnings: 1: parse_edid: unknown flag 1
OpenGL: renderer: AMD RV630 (DRM 2.50.0 / 5.10.57-antix.1-amd64-smp
LLVM 11.0.1)
v: 3.3 Mesa 20.3.5 compat-v: 3.0 direct render: Yes
Audio:
Device-1: Intel 82801H HD Audio vendor: Apple driver: snd_hda_intel v: kernel
bus-ID: 00:1b.0
chip-ID: 8086:284b class-ID: 0403
Sound Server-1: ALSA v: k5.10.57-antix.1-amd64-smp running: yes
Network:
Device-1: Broadcom BCM4321 802.11a/b/g/n vendor: Apple AirPort Extreme
driver: b43-pci-bridge
v: N/A modules: ssb,wl pcie: gen: 1 speed: 2.5 GT/s lanes: 1 bus-ID: 04:00.0
chip-ID: 14e4:4328
class-ID: 0280
Device-2: Marvell 88E8058 PCI-E Gigabit Ethernet driver: sky2 v: 1.30 pcie:
gen: 1
speed: 2.5 GT/s lanes: 1 port: 2000 bus-ID: 05:00.0 chip-ID: 11ab:436a class-
ID: 0200
IF: eth0 state: down mac: <filter>

IF-ID-1: wlan0 state: up mac: <filter>
IP v4: <filter> scope: global broadcast: <filter>
IP v6: <filter> scope: link
WAN IP: <filter>

Bluetooth:
Device-1: Apple Bluetooth HCI type: USB driver: btusb v: 0.8 bus-ID: 3-1:4 chip-ID: 05ac:8206
class-ID: fe01
Report: hciconfig ID: hci0 rfk-id: 1 state: down bt-service: running rfk-block: hardware: no
software: yes address: <filter>
Info: acl-mtu: 384:8 sco-mtu: 64:8 link-policy: rswitch hold sniff park
link-mode: slave accept

Logical:
Message: No logical block device data found.

RAID:
Message: No RAID data found.

Drives:
Local Storage: total: 465.76 GiB used: 4.62 GiB (1.0%)
SMART Message: Unable to run smartctl. Root privileges required.
ID-1: /dev/sda maj-min: 8:0 vendor: Seagate model: ST3500630AS Q size: 465.76 GiB block-size:
physical: 512 B logical: 512 B speed: 3.0 Gb/s type: N/A serial: <filter> rev: H
scheme: GPT
Optical-1: /dev/sr0 vendor: OPTIARC model: DVD RW AD-5630A rev: 1AHM
dev-links: cdrom,cdrw,dvd,dvdrw
Features: speed: 24 multisession: yes audio: yes dvd: yes rw: cd-r,cd-rw,dvd-r
state: running

Partition:
ID-1: / raw-size: 462.5 GiB size: 454.17 GiB (98.20%) used: 4.61 GiB (1.0%) fs: ext4
dev: /dev/sda2 maj-min: 8:2 label: rootantiX21 uuid: cca17cef-eb62-4687-abaa-49aa35a27503
ID-2: /boot/efi raw-size: 256 MiB size: 252 MiB (98.46%) used: 274 KiB (0.1%) fs: vfat
dev: /dev/sda1 maj-min: 8:1 label: EFI System uuid: C127-3F46

Swap:
Kernel: swappiness: 10 (default 60) cache-pressure: 50 (default 100)
ID-1: swap-1 type: partition size: 3 GiB used: 4.8 MiB (0.2%) priority: -2 dev: /dev/sda3
maj-min: 8:3 label: swapantiX uuid: f61da41d-a6de-4f7a-a5f8-1fe818687150

Unmounted:
Message: No unmounted partitions found.

USB:
Hub-1: 1-0:1 info: Full speed or root hub ports: 4 rev: 2.0 speed: 480 Mb/s chip-ID: 1d6b:0002
class-ID: 0900

Hub-2: 2-0:1 info: Full speed or root hub ports: 6 rev: 2.0 speed: 480 Mb/s chip-ID: 1d6b:0002

class-ID: 0900

Device-1: 2-4:3 info: Apple Built-in iSight type: Video driver: uvcvideo
interfaces: 3

rev: 2.0 speed: 480 Mb/s power: 500mA chip-ID: 05ac:8502 class-ID: 0e02
serial: <filter>

Hub-3: 3-0:1 info: Full speed or root hub ports: 2 rev: 1.1 speed: 12 Mb/s chip-ID: 1d6b:0001

class-ID: 0900

Device-1: 3-1:4 info: Apple Bluetooth HCI type: Bluetooth driver: btusb
interfaces: 3 rev: 2.0

speed: 12 Mb/s chip-ID: 05ac:8206 class-ID: fe01

Device-2: 3-2:3 info: Logitech Optical Wheel Mouse type: Mouse driver: hid-generic,usbhid

interfaces: 1 rev: 2.0 speed: 1.5 Mb/s power: 100mA chip-ID: 046d:c016 class-ID: 0301

Hub-4: 4-0:1 info: Full speed or root hub ports: 2 rev: 1.1 speed: 12 Mb/s chip-ID: 1d6b:0001

class-ID: 0900

Hub-5: 5-0:1 info: Full speed or root hub ports: 2 rev: 1.1 speed: 12 Mb/s chip-ID: 1d6b:0001

class-ID: 0900

Device-1: 5-1:2 info: Chicony KU-9908 Keyboard type: Keyboard,HID driver: hid-generic,usbhid

interfaces: 2 rev: 1.1 speed: 1.5 Mb/s power: 100mA chip-ID: 04f2:0111 class-ID: 0300

Hub-6: 6-0:1 info: Full speed or root hub ports: 2 rev: 1.1 speed: 12 Mb/s chip-ID: 1d6b:0001

class-ID: 0900

Hub-7: 7-0:1 info: Full speed or root hub ports: 2 rev: 1.1 speed: 12 Mb/s chip-ID: 1d6b:0001

class-ID: 0900

Device-1: 7-1:2 info: Apple Built-in IR Receiver type: HID driver: appleir,usbhid
interfaces: 1 rev: 2.0 speed: 1.5 Mb/s power: 100mA chip-ID: 05ac:8242 class-ID: 0300

Sensors:

System Temperatures: cpu: 58.0 C mobo: N/A gpu: radeon temp: 47.0 C

Fan Speeds (RPM): cpu: 1198

Repos:

Packages: apt: 1605 lib: 772

Active apt repos in: /etc/apt/sources.list.d/antix.list

1: deb h__p: //ftp.acc.umu.se/mirror/mxlinux.org/packages/antix/bullseye/
bullseye main nosystemd nonfree

Active apt repos in: /etc/apt/sources.list.d/bullseye-backports.list

1: deb h__p: //deb.debian.org/debian bullseye-backports main contrib non-free

Active apt repos in: /etc/apt/sources.list.d/debian-stable-updates.list

1: deb h__p: //mirrors.xtom.de/debian/ bullseye-updates main contrib non-free

Active apt repos in: /etc/apt/sources.list.d/debian.list

- 1: deb h__p: //mirrors.xtom.de/debian/ bullseye main contrib non-free
- 2: deb h__p: //security.debian.org/ bullseye-security main contrib non-free
- 3: deb h__p: //www.deb-multimedia.org testing main non-free

No active apt repos in: /etc/apt/sources.list.d/various.list

Processes:

CPU top: 5 of 152

- 1: cpu: 11.0% command: yad pid: 20523 mem: 26.1 MiB (1.3%)
- 2: cpu: 10.2% command: firefox-esr pid: 19685 mem: 179.3 MiB (9.0%)
- 3: cpu: 6.8% command: firefox-esr pid: 5878 mem: 490.7 MiB (24.7%)
- 4: cpu: 2.3% command: xorg pid: 1941 mem: 86.7 MiB (4.3%)
- 5: cpu: 1.6% command: gtdialog pid: 20490 mem: 26.9 MiB (1.3%)

Memory top: 5 of 152

- 1: mem: 490.7 MiB (24.7%) command: firefox-esr pid: 5878 cpu: 6.8%
- 2: mem: 232.4 MiB (11.7%) command: soffice.bin pid: 3898 cpu: 1.3%
- 3: mem: 179.3 MiB (9.0%) command: firefox-esr pid: 19685 cpu: 10.2%
- 4: mem: 107.6 MiB (5.4%) command: firefox-esr pid: 6021 cpu: 0.0%
- 5: mem: 90.6 MiB (4.5%) command: firefox-esr pid: 6053 cpu: 0.0%

Info:

Processes: 152 Uptime: 41m wakeups: 1 Init: SysVinit v: 2.96 runlevel: 5
default: 5

tool: service Compilers: gcc: 10.2.1 alt: 10 Client: shell wrapper v: 5.1.4-release
inxi: 3.3.19